
Features

- LC bandpass filter
- 50Ω single-ended operation
- ullet Surface Mounted Package (25mm imes 15.5mm imes 6.5mm)

Package Dimensions



Maximum Ratings

Parameter	Unit	Minimum	Typical	Maximum
Operating Temperature Range	$^{\circ}$ C	-40	25	85
Storage Temperature Range	$^{\circ}$ C	-40	25	85
Power Handling Capability	Watt	-	-	3.0

Electrostatics Sensitive Device (ESD)

	1 T F Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City,		IFL0128	33
			2014-10-	02
Integrated Technology Future	Gyounggi-Do, Korea 421-809	Rev.	AS 01	1/4

Specifications

Fo = 125MHz

	Minimum	Typical	Maximum	Unit
Center Frequency (Fo)	-	125	-	MHz
Insertion Loss (110~ 140MHz)	-	2.2	2.5	dB
Amplitude Ripple (110~ 140MHz)	-	0.3	0.6	dB
VSWR (110~ 140MHz)	-	1.3	1.5	-
Relative Attenuation @ 90 MHz @ 250 MHz	15.0 40.0	20.0 45.0	-	dB
Input/Output Impedance		50		Ohm

Notes:

- 1) All specifications are based on the matching schematic shown below, measured by Agilent Network analyzer and full 2 port calibration.
- 2) Electrical margin has been built into the design to account for the variations due to temperature drift and manufacturing tolerances
- 3) All attenuation measurements are measured relative to insertion loss

Integrated Technology Future

IIF Co., Lta.
102-901, Bucheon Technopark 364,
Samjeong-Dong, Ojeong-Gu, Bucheon-City,
Gyounggi-Do, Korea 421-809

Part No.	IFL01283		
Rev. Date	2014-10-02		
Rev.	AS 01	2/4	

Matching Schematic

(Actual matching values may vary due to PCB layout and parasitics)



Marking Configuration

Part No. 1)

- 1) Part Number
 - * Ink or Laser Marking available

Integrated Technol	oloav Future

ITF Co., Ltd.
102-901, Bucheon Technopark 364,
Samjeong-Dong, Ojeong-Gu, Bucheon-City,
Gyounggi-Do, Korea 421-809

Part No.	IFL01283		
Rev. Date	2014-10-02		
Rev.	AS 01	3/4	

Typical Performance (at 25℃)





ITF Co., Ltd.
102-901, Bucheon Technopark 364,
Samjeong-Dong, Ojeong-Gu, Bucheon-City,
Gyounggi-Do, Korea 421-809

Part No.	IFL01283		
Rev. Date	2014-10-02		
Rev.	AS 01	4/4	