

1. Features

- Typical 1dB bandwidth of 21.5 MHz
- High attenuation
- Single Ended Operation
- Surface Mounted Package (SMD)

RoHS Compliant


Tested by SGS Testing Korea

2. Electrical Specifications

Source and Load Impedance = 50Ω

Room Temperature : +25°C		Minimum	Typical	Maximum
Center Frequency (fo)	MHz	-	148.0	-
Insertion Loss	dB	-	22.0	23.5
1 dB Bandwidth	MHz	21.0	21.59	-
3dB Bandwidth	MHz	-	22.52	-
40dB Bandwidth	MHz	-	26.48	27.0
Amplitude Ripple (fo ± 10.0 MHz)	dB	-	0.6	1.0
Group Delay Variation (fo ± 10.0 MHz)	nsec	-	20	60
Absolute Delay	usec	-	1.08	-
Ultimate Rejection	dB	50	55	-
Temperature Coefficient of Frequency	ppm/°C	-72		

S1365 Package Dimension




Dimensions shown are nominal in millimeters

Body : Al₂O₃

Lid : Kovar, Ni Plated

Termination : Au plating 0.3 ~ 1.0um, over a 1.27 ~ 8.89um Ni Plating

Matching Schematic



Pin Configuration			
Input	11	Ground	6, 12
Output	5	Others	Ground

3. Typical Performance (at +25°C)

